



## TECHNICAL DATA

### STANDARD FITTING:

Homologate monoaxle trailer with rear lights and reflectors, automatic reverse gear, parking brakes, 14" road tyres with high load, ABS and Mudguards.  
Structure in steel section with hot dip galvanized.

### DIMENSIONS / WEIGHT :

Dimensions: length 3.370 – width 1.640 – height 1.530 mm approx  
Net weight: 900 kg. approx

### WATER PUMP H.P.:

➤ Brand: COMET  
➤ Model: TW Premium  
➤ Flow max: 20 l/min  
➤ Pressure max: 500 bar

### ENGINE:

➤ Brand: Kohler  
➤ Model: LDW 1404  
➤ Feeding: Diesel  
➤ Cooling: Liquid  
➤ Cylinders: 4  
➤ Displacement: 1372 cm<sup>3</sup>  
➤ Bore x stroke: 75 x 77,6 mm  
➤ Max power rating: 35,2 HP ( 26 kW)  
➤ Max engine rotation: 3.600 rpm

**Transmission:** Pulley and belts

C O M E T G R O U P

**BOARD PANEL:**

- Rev-indicator
- Hours counter
- Starting key
- Fuel level gauge
- Led high oil temperature
- Led low oil pressure
- Led air filter clogged
- Led alternator
- Led glow plugs
- Emergency button

**Electric panel:**

- Heater selector;
- "No-scale" device selector;
- Temperature regulation control;

**SAFETY REGULATION CONTROLS**

The equipment is completed with a safety valve to safe the high pressure line, one valve to regulate the pressure dimensioned on the operating range, one pressure gauge chosen on the same range.

**ALARM INSTALLED:**

- Sound alarm for too low water level in the tank
- Engine cut-off for lack water in the tank

**HEATER GROUP**

- Nr. 1 diesel heater, 12V;
- H.V. Transf. 12V;
- Safety system:
  - Flame control system;
  - Safety thermostat;
  - Temperature regulation by a potentiometer;
- " No-scale" device.

**H.P. HOSE REEL:**

- Type: Manual
- Material: Stainless steel
- Hose: Not included

**AUXILIARY HOSE REEL:**

- Type: Manual hose reel
- Material: Stainless steel
- Hose: Included - 35 m of low pressure hose 3/4" for feeding tank

**FUEL TANK:**

- Capacity: 75 lt approx. fuel only

	<b>JET TRAILER "JTR-H"</b> 20 l/min – 500 bar	2020_Rev.0
		Pagina 3
		Model: <b>JTR-H 20@500</b>

#### WATER FILTER

With washable cartridge and draining valve.  
Filtration degree: 50 mesh

#### WATER TANK

- Type: Fiberglass
- Capacity: 600 l
- Outfits: Front and rear Fiberglass cover

#### OPTIONAL ON REQUEST:

- 20/50 m of high pressure hose 3/8" for hot water application;
- Kit UNI 45 or Storz – Water hydrant connection for feeding tank;
- Working lamp;
- Graphic sticker for the cover.

#### ACCESSORIES ON REQUEST:

- Jetting gun with athermic and accident prevention handgrip;
- Lance with flat nozzle 15°;
- Lance with nozzle for steam;
- Lance with rotating nozzle;
- Lance with double head nozzle;
- Hydrosandblasting kit;
- Detergent dispenser kit;
- Floorwash kit;

#### DOCUMENTATION:

The unit comes fully tested with all fluids at correct level, provided with user manual in the English language, certificate of origin and CE compliance declaration.

All these data are referred to tests at sea level.

All the data taken back in this card are indicative and subject to modifications without notice in relation to technical and productive builder demands. The product/equipment described will be performed in accordance with technical details and standard PTC. For any special request or specify custom mount, these must be agreed under definition of the order. Any changes requested during construction will be charged thereafter.

C O M E T   G R O U P

P.T.C. S.r.l. via Mantegna, 4 – 42048 RUBIERA (RE) ITALY  
tel: +39 0522 1932911 fax: +39 0522 1932922  
e mail: info@ptcitaliana.com / info@masterfluid.it  
web: www.ptcitaliana.com / www.masterfluid.it  
R.E.A. RE-300083 - Reg. Impr. di Reggio Emilia n. 02057020998  
VAT no. IT 02057020998  
Capitale sociale euro 50.000 Cod. Fisc. e Partita IVA IT 02057020998  
Società soggetta al controllo e coordinamento di EMAK S.p.A.

